





				2		3		4		
	PRODUCT NUMBER 51939-928									
	NOTE: 3									
	NOTES:									
A	I. DIMENSIONS AND TOLERANCES ARE IN ACCORDANCE WITH ASME YI4.5M, 1994 UNLESS OTHERWISE SPECIFIED.									
	CONNECTOR	R NOTES:								
	POWEF	ING MATERIAL: UL 9 R CONTACT MATERIAI AL PIN MATERIAL: (L: COPPER ALI	LOY	THERMOPLASTIC					
	3. SEE 1 ⁻	TEM I & 2 IN PRIN	T 10064183 Fr	OR PLATING SPEC C)F 51939-928 AND 514	939-928LF RESPECTIVELY.				
В	4. MANUFACTURER'S NAME, DATE CODE AND OPTIONAL P/N TO APPEAR ON THIS SURFACE. THE MARK CAN BE OMITTED IF THERE IS NOT ENOUGH SPACE ON THIS SURFACE.									
		CT SPECIFICATION (CATION SPECIFICAT		67.						
	6. PACKA(GED IN TRAYS.								
	PCB NOT									
	7. ALL HC	OLE DIAMETERS ARE	FINISHED HOI	LE SIZE.						
/))	8. MOUNT	FING HOLES, WHERE	APPLICABLE,	ARE UNPLATED.						
c	9. ØI.I	51±0.025 DRILLED	HOLES PLATE) WITH						
	TO 0.	8 MIN SnPb OR Sn (.08 Cu PLATING TO 02±0.07 HOLE.								
ECI.	(10.) CONNE	ECTOR KEEP-OUT ZON	IE.							
yright	(II) DATUM AND BASIC DIMENIONS ARE ESTABLISHED BY CUSTOMER.									
Cop	_			d r De-Ming Lu	2014/10/27	projection		size	scale	
				eng De-Ming Lu	2014/11/14		MM	A 4	1:1	
D				chr - appr <mark>Pei-Ming Zher</mark>	 ng 2014/11/14	product family	PwrBlac	ecn no de rel level	Release	<u></u>
						24S + 3ACP			re	
					·	LE SOLDER HEADER	d k g	51939-92	28	4
				www.fci.com				mer Drw s	heet 4 of 4	_